

Certificate

kiwa

Certificate of conformity of
factory production control No. 3535/2024

AS Kiwa Latvia has granted this certificate as proof that

Ready-mixed concrete:

- 1) designed normal-weight concrete C8/10, C12/15, C16/20, C20/25, C25/30, C30/37, C35/45, C40/50, C45/55, C50/60, C55/67, C60/75, consistence classes S1 to S5, flow class F6,
- 2) self-compacting concrete (SCC) C25/30, C30/37, C35/45, C40/50, consistence class SF1 to SF3, resistance to water penetration up to W16, exposure classes: XC, XD, XS, XF, XA according to the Annex

PRODUCED BY:

SIA Heidelberg Materials Latvija Betons

Kroņa iela 5, Rīga, LV-1035, Latvia; reg. No. 40003250537

PLANT ADDRESS:

SIA Heidelberg Materials Latvija Betons, Rāmuļu iela 37, Rīga, LV-1005

CERTIFIED ACCORDING:

Certification scheme, based on initial inspection and approval of the factory and of the factory production control and the continuous surveillance, assessment and approval of the factory production control.

PRODUCT COMPLIES WITH THE REQUIREMENTS OF STANDARD:

EN 206+A2:2021 „Concrete - Specification, performance, production and conformity” and LVS 156-1:2022 „Concrete - Latvian National Annex to European standard EN 206 “Concrete - Specification, performance, production and conformity”

Certificate first issued on 9 April 2024 and remains valid as long as the conditions laid down in the above-mentioned standard, related provisions, the manufacturing conditions in the factory and the product specification of the certified type are not modified significantly.

7 May 2026

Mārtiņš Maskavs
Certification manager



Certificate issued on one page with Annex on one page



EN ISO/IEC 17065
S1-182

AS Kiwa Latvia
Skanstes iela 54, Rīga
LV-1013, Latvija

T. +371 67 607 900
latvia@kiwa.com

www.kiwa.com/lv

Annex

Certificate No. 3535/2024

Product: Designed ready-mixed normal weight and self-compacting concrete
Manufacturer: SIA „Heidelberg Materials Latvija Betons”, plant Rāmuļu iela 37, Rīga, LV-1005

| Characteristics | Declared properties | |
|--|---------------------|--------|
| | min | max |
| Coarsest aggregate size, mm | 4 | 32 |
| Chloride content, class | Cl 0,1 | Cl 0,2 |
| Consistence | | |
| slump classes | S1 | S5 |
| flow class | F6 | |
| slump-flow classes | SF1 | SF3 |
| Compressive strength class | | |
| normal-weight concrete | C8/10 | C60/75 |
| self-compacting concrete (SCC) | C25/30 | C40/50 |
| Resistance to water penetration | - | W16 |
| Exposure classes related to environmental actions | | |
| Corrosion induced by carbonation | XC1 | XC4 |
| Corrosion induced by chlorides other than from sea water | XD1 | XD3 |
| Corrosion induced by chlorides from sea water | XS1 | XS3 |
| Freeze/thaw attack | XF1 | XF4 |
| Aggressive chemical environment | XA1 | XA3 |

7 May 2026

Mārtiņš Maskavs
Certification manager



EN ISO/IEC 17065
S1-182

AS Kiwa Latvia
Skanstes iela 54, Rīga
LV-1013, Latvija

T. +371 67 607 900
latvia@kiwa.com

www.kiwa.com/lv